

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel. +39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =



Name: Axis 11 mm Rope	Code: 55251	Framing and Roofing Kit - Petzl
------------------------------	--------------------	--

Description

Semi-static rope with sewn termination with protective sheath to keep the connector in the right position and to facilitate manipulation. Also available in lengths from 10 to 50 m.

Excellent protection against abrasion.
Standard diameter, suitable for people with little or no experience of using rope techniques.

Technical Specifications:
Strength tied with a figure eight knot: 15 kN
Strength with sewn termination: 22 kN
Shock load (factor 0,3): 5.1 kN
Weight: 73 g/m

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 1891.
It is classified as PPE Cat. III.



Category III	Colours Yellow - Black	Available Sizes
Quantity/Carton 1	Important Information Read carefully the user sheet included. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.	Recommended for The device shall be used in combination with the other work-positioning devices in confined spaces.
Dexterity	EC Standards EN 1891 CE Type:A	Storage and cleaning Keep in a cool dry place, far from heat sources.